



1. Substrate designed to 1:40 falls (or flat with Tapered Insulation) primed with appropriate SIGNature Primer.
2. SIGNature Air and Vapour Control Layer.
3. IKOpro High Performance PU Adhesive for bonded Insulation.
4. SIGNature approved PIR Insulation, Tapered/Flatboard - thickness to achieve design U-value, designed to 1:40 falls as per BS6229:2018).
5. IKO Spectrabond Low Foam PU Adhesive / IKOpro Sprayfast FMA Adhesive for bonded membrane.
6. IKO Armourplan PSG / SG membrane.
7. Min. 60mm Hot Air Weld.
8. IKO Armourplan P / SM membrane.
9. IKO Armourplan Peel stop Bar fixed with appropriate IKOfix Fixings.
10. Timber Upstand - by others.
11. IKO Armourplan PVC Contact Adhesive / IKOpro Sprayfast PCA Adhesive for bonding none fleece backed membrane.
12. Armourplan membrane coated metal trim, mech fixed with appropriate IKOfix Fixings.
13. IKO Armourplan PVC Sealant.

The Waterproofing System should be installed in accordance with BS6229:2018 and Accuroof project Specification.

The details shown are indicative and for approval only and do not form part of any contract.

Data sheets for all IKO Polymeric and IKO PLC products are available on request.

Project specifications are available on request.

A	11/10/23	AT	Original Detail
Rev:	Date:	By:	Description:

# ACCUROOF

Unit 31F, Mannheim House, Gelders Hall Road,  
Shepshed, Loughborough, LE12 9NH  
Tel: 01509 501731  
Email: Technical@accuroof.co.uk  
Web: www.accuroof.co.uk

Drawing No:	SIG-ASG-04	Rev:	A
-------------	------------	------	---

Scale:	Not To Scale	Date:	11/10/2023
--------	--------------	-------	------------

Drawing: Abutment to Brickwork - Chased Joint Uninsulated