

	Substrate be smoot					ed falls, to ust,	
	greese ar	nd fro	ost, prin	ned wit	h SIGnat		
	Protect AVCL / Carrier Primer. SIGnature Ultra Protect approved Self						
	Adhesive	Carr	ier Mer	nbrane	e / Air & V	'apour	
	Control Layer (AVCL) overlapped at edges by						
	50-80mm and 150mm minimum at roll ends. AccuRoof Supplied Insulation bonded with						
						ve, primed	
	with SIGr						
	Primer.	1.114.	Drote	-+ Dee	0+ (1	-	
	SIGnature					no	
5.	SIGnature	e Ulti	a Prote	ect Cho	p Strand		
	Reinforcement minimum overlap of 50mm.						
	<ol> <li>SIGnature Ultra Protect Top Coat (1no application 1 of I/m<sup>2</sup> coverage for 20 year system or 2no applications of 0.75 I/m<sup>2</sup></li> </ol>						
	coverage	for 2	5 year	system	n, Each a <sub>l</sub>	pplication	
	of liquid needs to cure prior to applying the						
	next). 50mm ov	orlan	ofling	tand Li	iquid 8		
	Reinforce						
	Reinforce	men	t.				
	Render -			_			
	<ol> <li>9. Anti Corrosive Fixings.</li> <li>10.Brick joints to be Grouted flush and Brickwork</li> </ol>						
	primed wi						
	Multipurp	ose F	Primer.				
11.	Brickwork			, prime	d with ap	propriate	
Proj Data on r The do n	ractice. ect specifica a sheets for equest. details shor lot form part her informal be obtained	all Ac wn are t of an tion or	cuRoof s e indicati y contra n all Accu	supplied ve and f ct. uRoof pr	products a or approval oducts and	services	
А	28/04/22	PS	Origina	I Detail			
Rev:	Date:	By:	Descri	otion:			
	<b>′</b> \C	C	CU	R	00	OF	
	t 31F, Man					ad,	
Tel		50173	31		Π		
	ail: Technic b: www.ac			.co.uk			
Drawir	ng No:	SIG	SUP-18	}		Rev: A	
Scale:				Date:			
	Not To	Scal	е		28/04/2	022	
Drawir	ng:	SIGr	nature l	Iltro D	rotect		
		••••			Wall Def	tail	