

SIGNature Ultra Protect Fast-Drying PVC Primer

A Polyurethane Based primer designed to improve the adhesion between PVC based Membranes and SIGNature Ultra Protect Liquid waterproofing.

SUITABLE SURFACES

PVC Membranes.

FEATURES & BENEFITS

- Improves adhesion between PVC membranes and SIGNature Ultra Protect Liquid Waterproofing
- Simple application using a brush or roller
- Drying time of 20 minutes at 20°C

PRODUCT INFORMATION

Product Code	10701801
Size	5 litres €
Material	Polyurethane
Coverage	Up to 25m ² per 5 ltr tin
Colour	Clear
Application Temperature	5 - 30°C
Temperature Resistance Range	-30 - 70°C
Expected Cure Time (at 20°C)	20 minutes at 20°C
Shelf Life	12 months
Storage Instructions	The product should be stored unopened in a dry condition, away from direct sunlight.
Storage Temperature	5-25°C

Precautions

To be installed by Accuroof Registered Roofing Contractors (ARRC) only. Install to well ventilated areas only using the recommended equipment.

PREPARATION INSTRUCTIONS

Surface preparations

1. Test target surface to ensure substrate compatibility.
2. Surfaces must be clean, dry, and free from debris, fungal growth and any other contaminants before use.

Application Instructions

1. Apply SIGNature Ultra Protect Fast-Drying PVC Primer with a brush or roller, ensuring a uniform coverage of the substrate is achieved.
2. Allow primer to fully cure before applying SIGNature Ultra Protect Liquid Waterproofing (20-60 minutes dependent on ambient temperature).

Safety Data Sheet Available on Request