



SIGNature Air & Vapour Control Layer (Self Adhesive)

DoP Reference: SIGNature Air & Vapour Control Layer (Self Adhesive) CE DOP V4 August 2025

1. **UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE: 10401174**

2. **TYPE, BATCH OR SERIAL NUMBER OR OTHER ELEMENT ALLOWING IDENTIFICATION OF THE CONSTRUCTION PRODUCT – ARTICLE 11(4)**

Product Code	Reference Code	Nominal Dimensions	Nominal Weight kg/m ²
10401174	SG200600	1m x 15m	2.4

3. **INTENDED USE OR USES OF THE CONSTRUCTION PRODUCT, IN ACCORDANCE WITH THE APPLICABLE HARMONISED TECHNICAL SPECIFICATION**
Flexible sheets for waterproofing - Reinforced bitumen sheets for roof waterproofing

4. **NAME, REGISTERED TRADE NAME OR TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER – ARTICLE 11(5)**

SIGNature, Unit 31F, Mannheim House, Gelders Hall Industrial Estate, Shepshed, LE12 9NH

5. **NAME AND ADDRESS OF THE AUTHORISED REPRESENTATIVE WHOSE MANDATE COVERS THE TASKS SPECIFIED IN ARTICLE 12(2)**

SIG Trading (Ireland) Ltd - SIG House, First Floor, Ballymount Retail Centre, Dublin 24, D24 ED81, Ireland T: +353 1 623 4541

6. **SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF THE CONSTRUCTION PRODUCTS AS SET OUT IN ANNEX V**

2+

7. **NAME AND IDENTIFICATION NUMBER OF THE NOTIFIED BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A HARMONISED STANDARD**

2797 BSI Group The Netherlands B.V.

8. **NAME AND IDENTIFICATION NUMBER OF THE UK TECHNICAL ASSESSMENT BODY CONCERNING A CONSTRUCTION PRODUCT COVERED BY A TECHNICAL ASSESSMENT DOCUMENT**

N/A

9. **DECLARED PERFORMANCE ACCORDING TO: EN 13970:2004+A1:2006**

Characteristics	Result	Units	Tolerance	Ref. Norm
Reaction to fire	NPD	-	-	EN 13970:2004+A1:2006
Watertightness	Pass	-	-	
Nail tear length	130	N	-	
Nail tear width	180	N	-	
Tensile force length	550	N/50mm	± 20%	
Tensile force width	400	N/50mm	± 20%	
Elongation length	20	%	± 1	
Elongation width	25	%	± 1	
Resistance to impact	NPD	-	-	
Resistance to tearing length	NPD	N	-0;-	
Resistance to tearing width	NPD	N	-0;-	
Peel resistance to joints initial: length/width	NPD	N/50 mm	-0;-	
Shear resistance of joints: initial	NPD	N/50 mm	-0;-	
Low temperature flexibility	≤ 10	°C	-	
Watertightness after artificial ageing	Pass	-	-	
Chemical resistance	-	-	-	
Water vapour resistance	2436	Sd value (m)	-	
Danger Substances (Note 2)				

NPD = No Performance Declared

Note 1: Since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the product alone.

Note 2: In absence of test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.

The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of SIGNature, SIG Trading Ltd:

Duncan Winter - Commercial Director
SIG Trading Ltd, St Ives - 26/08/25